



# 26.5-40GHz 100W SOLID STATE HIGH POWER AMPLIFIER RACKMOUNT LPA26404950RM

## FEATURES

- Wide Bandwidth
- Low Power Consumption
- Low Noise Figure
- Miniature Sizes, Field Removable connector
- Compact/Rugged Thin-Film Construction

## APPLICATIONS

- Microwave Radio & VSAT
- Military & Space
- Test Instrumentation
- Fiber Optics

## ELECTRICAL SPECIFICATIONS@25°C:

Parameter	Min	Typical	Max	Units
Frequency Range	26.5		40	GHz
Power Gain	49			dB
Power Gain Flatness		±4		dB
Output Power(Psat CW)	100			Watt
pulse Width	0.1		100	us
PRF	50Hz		100KHz	
Spurious	-50			dBc
Harmonics	-20			dBc
Noise Figure				dBm/MHz
Input VSWR			2:1	Ratio
Output VSWR			2.5:1	Ratio
Input Voltage	180	220	240	Volt
Human-computer Interface	touch screen LCD:Voltage,Current, Temperature,FWD/REV Power			
Program Control Interface	TCP/IP and Ethernet			

Note:

- 1.Input Signal:AM, FM, CW, Pulse, LFM, Phase coded.
- 2.Over Temperature Protection; Over REV VSWR Protection; Over incentive protection.
- 3.Air forced cool.

## ENVIRONMENTAL RATINGS:

Parameter	Min	Typical	Max	Units
Max Input power		0±6		dBm
Operating Temperature	0		+40	°C
Non-operating Temperature	-40		+85	°C
Relative humidity (non-condensing)		95		%
Altitude (MIL-STD-810F)	10000		30000	feet
Shock / Vibration (MIL-STD-810F)		Airbone		



26.5-40GHz 100W SOLID STATE HIGH POWER AMPLIFIER  
RACKMOUNT LPA26404950RM

**MECHANICAL SPECIFICATIONS:**

Parameter	Value	Limits	Units
Dimensions	6U D:500mm	Max	Milimeter
Weight	55	Max	Kg
RF Connectors Input	2.92mm-F		
RF Connectors Output	WR-28		
Forward / Reverse Detection Connectors	2.92mm-F		
Impedance			ohms

**OUTLINE DRAWING(mm):**

